



ANKOLUX AQUA BASE STAIN VC-D (COLOUR)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878
Issue date: 13-06-2022 Revision date: 16-08-2022 Supersedes version of: 05-07-2022 Version: 4.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : ANKOLUX AQUA BASE STAIN VC-D (COLOUR)
Product code : 16-0201-000
Type of product : Paint
Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use, Industrial use

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Manufacturer

Anker Stuy Verven B.V.
Hellingwal , 1
NL- 8407 EM Terwispel
Netherlands
T +31 (0) 513 - 465 000
info@ankerstuy.nl - www.ankerstuy.nl

1.4. Emergency telephone number

Country	Organisation/Company	Address	Emergency number	Comment
United Kingdom	Guy's & St Thomas' Poisons Unit Medical Toxicology Unit, Guy's & St Thomas' Hospital Trust	Avonley Road SE14 5ER London	+44 20 7188 7188	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

Adverse physicochemical, human health and environmental effects

To our knowledge, this product does not present any particular risk, provided it is handled in accordance with good occupational hygiene and safety practice.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

EUH-statements : EUH066 - Repeated exposure may cause skin dryness or cracking.
EUH208 - Contains reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)(55965-84-9). May produce an allergic reaction.
EUH210 - Safety data sheet available on request.

2.3. Other hazards

Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

ANKOLUX AQUA BASE STAIN VC-D (COLOUR)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	Conc.	Classification according to Regulation (EC) No. 1272/2008 [CLP]
2-butoxyethanol; ethylene glycol monobutyl ether substance with national workplace exposure limit(s) (DE, ES, FR, NL, PL); substance with a Community workplace exposure limit	CAS-No.: 111-76-2 EC-No.: 203-905-0 EC Index-No.: 603-014-00-0 REACH-no: 01-2119475108-36	1 – 2,5	Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Irrit. 2, H319
N-methyl-2-pyrrolidone, 1-methyl-2-pyrrolidone substance listed as REACH Candidate (1-Methyl-2-pyrrolidone) substance with national workplace exposure limit(s) (DE, ES, FR, NL, PL); substance with a Community workplace exposure limit	CAS-No.: 872-50-4 EC-No.: 212-828-1 EC Index-No.: 606-021-00-7 REACH-no: 01-2119472430-46	0,1 – 1	Repr. 1B, H360D Eye Irrit. 2, H319 STOT SE 3, H335 Skin Irrit. 2, H315
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	CAS-No.: 55965-84-9 EC Index-No.: 613-167-00-5	< 0,1	Acute Tox. 2 (Inhalation), H330 Acute Tox. 2 (Dermal), H310 Acute Tox. 3 (Oral), H301 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=100)

Specific concentration limits:

Name	Product identifier	Specific concentration limits
N-methyl-2-pyrrolidone, 1-methyl-2-pyrrolidone	CAS-No.: 872-50-4 EC-No.: 212-828-1 EC Index-No.: 606-021-00-7 REACH-no: 01-2119472430-46	(10 ≤C ≤ 100) STOT SE 3, H335
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	CAS-No.: 55965-84-9 EC Index-No.: 613-167-00-5	(0,0015 ≤C ≤ 100) Skin Sens. 1A, H317 (0,06 ≤C < 0,6) Skin Irrit. 2, H315 (0,06 ≤C < 0,6) Eye Irrit. 2, H319 (0,6 ≤C ≤ 100) Eye Dam. 1, H318 (0,6 ≤C ≤ 100) Skin Corr. 1C, H314

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact	: Repeated exposure may cause skin dryness or cracking.
-------------------------------------	---

ANKOLUX AQUA BASE STAIN VC-D (COLOUR)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : PBM-code: B.

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Wear personal protective equipment.

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool.

7.3. Specific end use(s)

No additional information available

ANKOLUX AQUA BASE STAIN VC-D (COLOUR)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

2-butoxyethanol; ethylene glycol monobutyl ether (111-76-2)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	2-Butoxyethanol
IOEL TWA	98 mg/m ³
IOEL TWA [ppm]	20 ppm
IOEL STEL	246 mg/m ³
IOEL STEL [ppm]	50 ppm
Remark	Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
France - Occupational Exposure Limits	
Local name	2-Butoxyéthanol (Butylglycol)
VME (OEL TWA)	49 mg/m ³
VME (OEL TWA) [ppm]	10 ppm
VLE (OEL C/STEL)	246 mg/m ³
VLE (OEL C/STEL) [ppm]	50 ppm
Remark	Valeurs réglementaires contraignantes; risque de pénétration percutanée
Regulatory reference	Article R4412-149 du Code du travail (réf.: INRS ED 984, 2016; Décret n° 2019-1487; Décret n° 2020-1546; Décret n° 2021-434; Décret n° 2021-1849)
Germany - Occupational Exposure Limits (TRGS 900)	
Local name	2-Butoxyethanol
AGW (OEL TWA) [1]	49 mg/m ³
AGW (OEL TWA) [2]	10 ppm
Peak exposure limitation factor	2(l)
Remark	EU - Europäische Union (Von der EU wurde ein Luftgrenzwert festgelegt: Abweichungen bei Wert und Spitzenbegrenzung sind möglich); DFG - Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe der DFG (MAK-Kommission); H - hautresorptiv; Y - Ein Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes (BGW) nicht befürchtet zu werden
Regulatory reference	TRGS900
Germany - Biological limit values (TRGS 903)	
Local name	2-Butoxyethanol
Biological limit value	150 mg/g creatinine Parameter: Butoxyessigsäure (nach Hydrolyse) - Untersuchungsmaterial: U = Urin - Probenahmezeitpunkt: b) Expositionsende, bzw. Schichtende, c) bei Langzeitexposition: am Schichtende nach mehreren vorangegangenen Schichten - Festlegung/Begründung: 11/2016 DFG
Regulatory reference	TRGS 903
Netherlands - Occupational Exposure Limits	
Local name	2-Butoxyethanol
TGG-8u (OEL TWA)	100 mg/m ³

ANKOLUX AQUA BASE STAIN VC-D (COLOUR)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

2-butoxyethanol; ethylene glycol monobutyl ether (111-76-2)	
TGG-15min (OEL STEL)	246 mg/m ³
Remark	H (Huidopname) Stoffen die relatief gemakkelijk door de huid kunnen worden opgenomen, hetgeen een substantiële bijdrage kan betekenen aan de totale inwendige blootstelling, hebben in de lijst een H-aanduiding. Bij deze stoffen moeten naast maatregelen tegen inademing ook adequate maatregelen ter voorkoming van huidcontact worden genomen.
Regulatory reference	Arbeidsomstandighedenregeling 2022
Poland - Occupational Exposure Limits	
Local name	2-Butoksyetanol (butoksyetylowy alkohol)
NDS (OEL TWA)	98 mg/m ³
NDSCh (OEL STEL)	200 mg/m ³
Remark	Skóra (Oznakowanie substancji notacją „skóra” oznacza, że wchłanianie substancji przez skórę może być tak samo istotne jak przy narażeniu drogą oddechową).
Regulatory reference	Dz. U. 2018 poz. 1286
Spain - Occupational Exposure Limits	
Local name	2-Butoxietanol (Butil cellosolve; Éter monobutílico del etilenglicol)
VLA-ED (OEL TWA) [1]	98 mg/m ³
VLA-ED (OEL TWA) [2]	20 ppm
VLA-EC (OEL STEL)	245 mg/m ³
VLA-EC (OEL STEL) [ppm]	50 ppm
Remark	Vía dérmica (Indica que, en las exposiciones a esta sustancia, la aportación por la vía cutánea puede resultar significativa para el contenido corporal total si no se adoptan medidas para prevenir la absorción. En estas situaciones, es aconsejable la utilización del control biológico para poder cuantificar la cantidad global absorbida del contaminante), VLI (Agente químico para el que la U.E. estableció en su día un valor límite indicativo), VLB® (Agente químico que tiene Valor Límite Biológico).
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2022. INSHT
Spain - Biological limit values	
Local name	2-Butoxietanol (Butil cellosolve; Éter monobutílico del etilenglicol)
BLV	200 mg/g creatinine Parámetro: Ácido butoxiacético - Medio: Orina - Momento de muestreo: Final de la jornada laboral - Notas: Con hidrólisis
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2022. INSHT
N-methyl-2-pyrrolidone, 1-methyl-2-pyrrolidone (872-50-4)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	n-Methyl-2-pyrrolidone
IOEL TWA	40 mg/m ³
IOEL STEL	80 mg/m ³
IOEL STEL [ppm]	20 ppm
Remark	Skin
Regulatory reference	COMMISSION DIRECTIVE 2009/161/EU
EU - Binding Occupational Exposure Limit (BOEL)	
Local name	1-Methyl-2-pyrrolidone
BOEL TWA	40 mg/m ³

ANKOLUX AQUA BASE STAIN VC-D (COLOUR)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

N-methyl-2-pyrrolidone, 1-methyl-2-pyrrolidone (872-50-4)	
BOEL TWA [ppm]	10 ppm
BOEL STEL	80 mg/m ³
BOEL STEL [ppm]	20 ppm
Notes	Skin (Substantial contribution to the total body burden via dermal exposure possible)
Regulatory reference	DIRECTIVE (EU) 2022/431 (amending Directive 2004/37/EC)
EU - Biological Limit Value (BLV)	
Local name	N-Methyl-2-pyrrolidone
BLV	20 mg/g creatinine Parameter: 2-hydroxy-N-methylsuccinimide - Medium: urine - Sampling time: morning-after-shift ; 18 hours 70 mg/g creatinine Parameter: 5-hydroxy-N-methyl-2-pyrrolidone - Medium: urine - Sampling time: 2-4 hours after the end of exposure/shift
Regulatory reference	SCOEL List of recommended health-based BLVs and BGVs
France - Occupational Exposure Limits	
Local name	N-Méthyl-2-pyrrolidone
VME (OEL TWA)	40 mg/m ³
VME (OEL TWA) [ppm]	10 ppm
VLE (OEL C/STEL)	80 mg/m ³
VLE (OEL C/STEL) [ppm]	20 ppm
Remark	Valeurs réglementaires indicatives; risque de pénétration percutanée; substance classée toxique pour la reproduction de catégorie 1B
Regulatory reference	Arrêté du 30 juin 2004 modifié (réf.: INRS ED 984, 2016)
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA) [1]	82 mg/m ³
AGW (OEL TWA) [2]	20 ppm
Peak exposure limitation factor	2(l)
Remark	EU - Europäische Union (Von der EU wurde ein Luftgrenzwert festgelegt: Abweichungen bei Wert und Spitzenbegrenzung sind möglich); DFG - Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe der DFG (MAK-Kommission); AGS - Ausschuss für Gefahrstoffe; H - hautresorptiv; Y - Ein Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes (BGW) nicht befürchtet zu werden; 11 - Summe aus Dampf und Aerosolen; 19 - Die Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe der DFG hat in der MAK- und BAT-Werte-Liste zum gleichlautenden MAK-Wert auch einen BAT-Wert festgelegt; 32 - Gemäß Änderung von Anhang XVII der Verordnung (EG) Nr. 1907/2006 (https://eur-lex.europa.eu/legal-content/DE/TXT/PDF/?uri=CELEX:32018R0588&from=DE) gilt ab 10. Mai 2020 eine Verwendungsbeschränkung für NMP, wenn der dort genannte Luftgrenzwert nicht eingehalten wird
Regulatory reference	TRGS900
Germany - Biological limit values (TRGS 903)	
Local name	N-Methyl-2-pyrrolidon
Biological limit value	150 mg/l Parameter: 5-Hydroxy- N-methyl-2-pyrrolidon - Untersuchungsmaterial: U = Urin - Probenahmezeitpunkt: b) Expositionsende, bzw. Schichtende - Festlegung/Begründung: 05/2013 DFG
Regulatory reference	TRGS 903

ANKOLUX AQUA BASE STAIN VC-D (COLOUR)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

N-methyl-2-pyrrolidone, 1-methyl-2-pyrrolidone (872-50-4)	
Netherlands - Occupational Exposure Limits	
Local name	N-Methyl-2-pyrrolidon
TGG-8u (OEL TWA)	40 mg/m ³
TGG-15min (OEL STEL)	80 mg/m ³
Remark	H (Huidopname) Stoffen die relatief gemakkelijk door de huid kunnen worden opgenomen, hetgeen een substantiële bijdrage kan betekenen aan de totale inwendige blootstelling, hebben in de lijst een H-aanduiding. Bij deze stoffen moeten naast maatregelen tegen inademing ook adequate maatregelen ter voorkoming van huidcontact worden genomen.
Regulatory reference	Arbeidsomstandighedenregeling 2022
Poland - Occupational Exposure Limits	
Local name	1-Metylo-2-pirolidon
NDS (OEL TWA)	40 mg/m ³
NDSch (OEL STEL)	80 mg/m ³
Remark	Skóra (Oznakowanie substancji notacją „skóra” oznacza, że wchłanianie substancji przez skórę może być tak samo istotne jak przy narażeniu drogą oddechową).
Regulatory reference	Dz. U. 2018 poz. 1286
Spain - Occupational Exposure Limits	
Local name	N-Metil-2-pirrolidona
VLA-ED (OEL TWA) [1]	40 mg/m ³
VLA-ED (OEL TWA) [2]	10 ppm
VLA-EC (OEL STEL)	80 mg/m ³
VLA-EC (OEL STEL) [ppm]	20 ppm
Remark	Vía dérmica (Indica que, en las exposiciones a esta sustancia, la aportación por la vía cutánea puede resultar significativa para el contenido corporal total si no se adoptan medidas para prevenir la absorción. En estas situaciones, es aconsejable la utilización del control biológico para poder cuantificar la cantidad global absorbida del contaminante), VLI (Agente químico para el que la U.E. estableció en su día un valor límite indicativo), VLB® (Agente químico que tiene Valor Límite Biológico), TR1B (Cuando las pruebas utilizadas para la clasificación procedan principalmente de datos en animales), r (Esta sustancia tiene establecidas restricciones a la fabricación, la comercialización o el uso en los términos especificados en el “Reglamento (CE) nº 1907/2006 sobre Registro, Evaluación, Autorización y Restricción de sustancias y preparados químicos” (REACH) de 18 de diciembre de 2006 (DOUE L 369 de 30 de diciembre de 2006). Las restricciones de una sustancia pueden aplicarse a todos los usos o sólo a usos concretos. El anexo XVII del Reglamento REACH contiene la lista de todas las sustancias restringidas y especifica los usos que se han restringido).
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2022. INSHT
Spain - Biological limit values	
Local name	N-Metil-2-pirrolidona
BLV	20 mg/g creatinine Parámetro: 2-hidroxi-N-metilsuccinimida - Medio: orina - Momento de muestreo: Antes de la jornada laboral 70 mg/g creatinine Parámetro: 5-hidroxi-N-metil-2-pirrolidona - Medio: orina - Momento de muestreo: Entre 2 y 4 horas después del final la exposición
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2022. INSHT

8.1.2. Recommended monitoring procedures

No additional information available

ANKOLUX AQUA BASE STAIN VC-D (COLOUR)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

2-butoxyethanol; ethylene glycol monobutyl ether (111-76-2)	
DNEL/DMEL (Workers)	
Acute - systemic effects, inhalation	1091 mg/m ³
Acute - local effects, inhalation	246 mg/m ³
Long-term - systemic effects, inhalation	98 mg/m ³
DNEL/DMEL (General population)	
Acute - systemic effects, inhalation	426 mg/m ³
Acute - systemic effects, oral	26,7 mg/kg bodyweight/day
Acute - local effects, inhalation	147 mg/m ³
Long-term - systemic effects, oral	6,3 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	59 mg/m ³
PNEC (Water)	
PNEC aqua (freshwater)	8,8 mg/l
PNEC aqua (marine water)	0,88 mg/l
PNEC aqua (intermittent, freshwater)	26,4 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	34,6 mg/kg dwt
PNEC sediment (marine water)	3,46 mg/kg dwt
PNEC (Soil)	
PNEC soil	2,33 mg/kg dwt
PNEC (Oral)	
PNEC oral (secondary poisoning)	0,02 g/kg food
PNEC (STP)	
PNEC sewage treatment plant	463 mg/l
N-methyl-2-pyrrolidone, 1-methyl-2-pyrrolidone (872-50-4)	
DNEL/DMEL (Workers)	
Acute - systemic effects, dermal	208 mg/kg bodyweight/day
Acute - systemic effects, inhalation	80 mg/m ³
Long-term - systemic effects, dermal	4,8 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	14,4 mg/m ³
Long-term - local effects, inhalation	40 mg/m ³
DNEL/DMEL (General population)	
Acute - systemic effects, dermal	125 mg/kg bodyweight/day
Acute - systemic effects, inhalation	80 mg/m ³
Acute - systemic effects, oral	26 mg/kg bodyweight/day
Long-term - systemic effects, oral	0,85 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	3,6 mg/m ³

ANKOLUX AQUA BASE STAIN VC-D (COLOUR)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

N-methyl-2-pyrrolidone, 1-methyl-2-pyrrolidone (872-50-4)	
Long-term - systemic effects, dermal	2,4 mg/kg bodyweight/day
Long-term - local effects, inhalation	4,5 mg/m ³
PNEC (Water)	
PNEC aqua (freshwater)	0,25 mg/l
PNEC aqua (marine water)	0,025 mg/l
PNEC aqua (intermittent, freshwater)	5 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	1,09 mg/kg dwt
PNEC sediment (marine water)	0,109 mg/kg dwt
PNEC (Soil)	
PNEC soil	0,0701 mg/kg dwt
PNEC (Oral)	
PNEC oral (secondary poisoning)	0,00167 g/kg food
PNEC (STP)	
PNEC sewage treatment plant	10 mg/l
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (55965-84-9)	
DNEL/DMEL (Workers)	
Acute - local effects, inhalation	0,04 mg/m ³
Long-term - local effects, inhalation	0,02 mg/m ³
DNEL/DMEL (General population)	
Acute - systemic effects, oral	0,11 mg/kg bodyweight/day
Acute - local effects, inhalation	0,04 mg/m ³
Long-term - systemic effects, oral	0,09 mg/kg bodyweight/day
Long-term - local effects, inhalation	0,02 mg/m ³
PNEC (Water)	
PNEC aqua (freshwater)	3,39 µg/l
PNEC aqua (marine water)	3,39 µg/l
PNEC aqua (intermittent, freshwater)	3,39 µg/l
PNEC aqua (intermittent, marine water)	3,39 µg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	0,027 mg/kg dwt
PNEC sediment (marine water)	0,027 mg/kg dwt
PNEC (Soil)	
PNEC soil	0,01 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	0,23 mg/l

8.1.5. Control banding

No additional information available

ANKOLUX AQUA BASE STAIN VC-D (COLOUR)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Safety glasses

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Protective gloves

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: No data available
Odour	: No data available
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: > 60 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Relative vapour density at 20°C	: No data available
Relative density	: No data available
Density	: 1,014 g/cm ³
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available

ANKOLUX AQUA BASE STAIN VC-D (COLOUR)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Oxidising properties : No data available
Explosive limits : No data available

9.2. Other information

VOC content : 20 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

2-butoxyethanol; ethylene glycol monobutyl ether (111-76-2)

LD50 oral	1414 mg/kg bodyweight Animal: guinea pig, Guideline: OECD Guideline 401 (Acute Oral Toxicity), 95% CL: 1020 - 1961
LD50 dermal rat	> 2000 mg/kg Source: ECHA

N-methyl-2-pyrrolidone, 1-methyl-2-pyrrolidone (872-50-4)

LD50 oral rat	4150 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity), 95% CL: 3100 - 5560
LD50 dermal rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	> 5,1 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (55965-84-9)

LD50 oral rat	64 – 561 mg/kg
LD50 dermal rat	> 1008 mg/kg bodyweight Animal: rat, Guideline: EPA OPP 81-2 (Acute Dermal Toxicity), Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LD50 dermal rabbit	200 mg/kg Source: US EPA
LC50 Inhalation - Rat	171 – 2360 mg/m ³
LC50 Inhalation - Rat (Dust/Mist)	0,33 mg/l Source: US EPA

ANKOLUX AQUA BASE STAIN VC-D (COLOUR)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

2-butoxyethanol; ethylene glycol monobutyl ether (111-76-2)

IARC group	3 - Not classifiable
------------	----------------------

N-methyl-2-pyrrolidone, 1-methyl-2-pyrrolidone (872-50-4)

NOAEL (chronic, oral, animal/male, 2 years)	≈ 89 mg/kg bodyweight Animal: mouse, Animal sex: male, Guideline: OECD Guideline 451 (Carcinogenicity Studies), Guideline: EU Method B.32 (Carcinogenicity Test), Guideline: EPA OTS 798.3300 (Carcinogenicity), Remarks on results: other:
NOAEL (chronic, oral, animal/female, 2 years)	≈ 221 mg/kg bodyweight Animal: mouse, Animal sex: female, Guideline: OECD Guideline 451 (Carcinogenicity Studies), Guideline: EU Method B.32 (Carcinogenicity Test), Guideline: EPA OTS 798.3300 (Carcinogenicity), Remarks on results: other:

Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified

N-methyl-2-pyrrolidone, 1-methyl-2-pyrrolidone (872-50-4)

STOT-single exposure	May cause respiratory irritation.
----------------------	-----------------------------------

STOT-repeated exposure	: Not classified
------------------------	------------------

2-butoxyethanol; ethylene glycol monobutyl ether (111-76-2)

NOAEL (dermal, rat/rabbit, 90 days)	> 150 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study), Remarks on results: other:
-------------------------------------	---

N-methyl-2-pyrrolidone, 1-methyl-2-pyrrolidone (872-50-4)

LOAEL (dermal, rat/rabbit, 90 days)	1653 mg/kg bodyweight Animal: rabbit, Animal sex: male, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)
LOAEC (inhalation, rat,dust/mist/fume, 90 days)	1 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)
NOAEL (dermal, rat/rabbit, 90 days)	826 mg/kg bodyweight Animal: rabbit, Animal sex: male, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	0,5 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (55965-84-9)

LOAEL (dermal, rat/rabbit, 90 days)	0,525 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: EPA OPP 82-3 (Subchronic Dermal Toxicity 90 Days)
-------------------------------------	--

Aspiration hazard	: Not classified
-------------------	------------------

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified
Not rapidly degradable	

ANKOLUX AQUA BASE STAIN VC-D (COLOUR)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

2-butoxyethanol; ethylene glycol monobutyl ether (111-76-2)	
LC50 - Fish [1]	1474 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	≈ 1800 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	911 mg/l Source: ECHA
NOEC (chronic)	100 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	≥ 100 mg/l Test organisms (species): Oryzias latipes Duration: '14 d'
N-methyl-2-pyrrolidone, 1-methyl-2-pyrrolidone (872-50-4)	
LC50 - Fish [1]	> 500 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 72h - Algae [1]	600,5 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
EC50 72h - Algae [2]	672,8 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
LOEC (chronic)	25 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	12,5 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (55965-84-9)	
LC50 - Fish [1]	0,19 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
LC50 - Fish [2]	0,28 mg/l Test organisms (species): Lepomis macrochirus
EC50 - Crustacea [1]	0,16 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	6,3 – 27,3 µg/l
NOEC (chronic)	0,1 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	0,098 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '28 d'

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

2-butoxyethanol; ethylene glycol monobutyl ether (111-76-2)	
Partition coefficient n-octanol/water (Log Pow)	0,81 Source: ECHA

12.4. Mobility in soil

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (55965-84-9)	
Mobility in soil	12,08 Source: EPISUITE

12.5. Results of PBT and vPvB assessment

Component	
N-methyl-2-pyrrolidone, 1-methyl-2-pyrrolidone (872-50-4)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

12.6. Other adverse effects

No additional information available

ANKOLUX AQUA BASE STAIN VC-D (COLOUR)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.2. UN proper shipping name				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport hazard class(es)				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
No supplementary information available				

14.6. Special precautions for user

Overland transport

Not applicable

Transport by sea

Not applicable

Air transport

Not applicable

Inland waterway transport

Not applicable

Rail transport

Not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

Contains substance(s) listed on the REACH Candidate List in concentrations $\geq 0.1\%$ or SCL: 1-Methyl-2-pyrrolidone (EC 212-828-1, CAS 872-50-4)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

ANKOLUX AQUA BASE STAIN VC-D (COLOUR)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)
Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)
VOC content : 20 g/l

Directive 2004/42/EC on the limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing products:

EU limit value for ANKOLUX AQUA BASE STAIN VC-D (COLOUR) (cat. A/d): 130 g/l.

ANKOLUX AQUA BASE STAIN VC-D (COLOUR) Contains max 20,00 g/l VOC.

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

France	
Occupational diseases	
Code	Description
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide

Germany

Employment restrictions : Observe restrictions according Act on the Protection of Working Mothers (MuSchG)
Observe restrictions according Act on the Protection of Young People in Employment (JArbSchG)

Water hazard class (WGK) : WGK 3, Highly hazardous to water (Classification according to AwSV, Annex 1)

Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

ABM category : Z(1) - non biodegradable substances with hazardous properties for humans and the environment (carcinogenicity/ mutagenicity/ reprotoxicity/bioaccumulative potential/ toxicity or persistence)

SZW-lijst van kankerverwekkende stoffen : None of the components are listed

SZW-lijst van mutagene stoffen : None of the components are listed

SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed

SZW-lijst van reprotoxische stoffen – Vruchtbaarheid : None of the components are listed

SZW-lijst van reprotoxische stoffen – Ontwikkeling : N-methyl-2-pyrrolidone, 1-methyl-2-pyrrolidone is listed

Denmark

Classification remarks : Emergency management guidelines for the storage of flammable liquids must be followed

Danish National Regulations : Pregnant/breastfeeding women working with the product must not be in direct contact with the product

Switzerland

Storage class (LK) : LK 10/12 - Liquids

CH - VOC (SR 814.018) : 2,1917791 %

15.2. Chemical safety assessment

A chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor

ANKOLUX AQUA BASE STAIN VC-D (COLOUR)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Abbreviations and acronyms:	
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development, OECD
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Full text of H- and EUH-statements:	
Acute Tox. 2 (Dermal)	Acute toxicity (dermal), Category 2
Acute Tox. 2 (Inhalation)	Acute toxicity (inhal.), Category 2
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1

ANKOLUX AQUA BASE STAIN VC-D (COLOUR)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH208	Contains reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)(55965-84-9). May produce an allergic reaction.
EUH210	Safety data sheet available on request.
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H360D	May damage the unborn child.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
Repr. 1B	Reproductive toxicity, Category 1B
Skin Corr. 1C	Skin corrosion/irritation, Category 1, Sub-Category 1C
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1A	Skin sensitisation, category 1A
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.